

JUMPAX

BRIEF DESCRIPTION FOR SPECIFIERS

Jumpax is a unique and highly versatile underlay, instantly producing a perfect, stable surface for stuck-down floor finishes. As a floating double layered fibreboard system it combines speed and ease of use with excellent smoothing capacity and the ability to overcome many time-consuming difficulties associated with traditional surface preparation methods. It requires no screeds, glues, nails or other fixings and is ideal for use on both solid and timber floor constructions. It requires no drying or setting time as with screeding systems, no priming, no mixing, no rubbing down and it has no smell. It is not necessary to remove old floor coverings or surface coatings, which can be overlaid, nor is it necessary to decontaminate concrete in order to achieve a good bond, as the floating floor principle employed does not require any kind of fixing or bonding to the substrate. This also means that future removal of both floor-covering and underlay is quick, clean and easy, with no residues or damage whatsoever to the old floor surface, or previous floor finish.

Jumpax should always be installed over a polythene moisture vapour barrier, minimum 150 micron (600 gauge) thickness. The overall thickness of only 10 mm makes it feasible to overlay existing floorings in most situations. This includes an integral cushioning layer, which enables it to accommodate irregularities of up to 3 mm in the sub-floor and also provides excellent acoustic and thermal insulation.

The speed and simplicity of Jumpax together with the elimination of previously unavoidable processes results in the shortest possible overall installation time.

With a minimum level of skill and the simplest of tools JUMPAX can be installed to the same high standard and quality of surface finish every time it is used. The saving of considerable time and return visits needed for screeds to dry makes it easy to plan schedules and timetables and eliminates wasted time on site. There are no delays because the panels are pre-coated with an interactive adhesive which bonds the two layers together instantly and permanently with firm contact. Sanding down any minor imperfections at the joints with fine 120 grit sandpaper and vacuuming out, are all that is necessary prior to setting out and installing the floor finish.

In contract situations, with various trades and tight deadlines, Jumpax can be installed in sections and immediately covered with flooring, enabling work to progress with an absolute minimum of disruption.